

BRAKE & CLUTCH FLUID

Brake Oil
DOT3



BRAKE & CLUTCH FLUID, designed for use in conventional hydraulic brake and clutch systems under normal service conditions, particularly service conditions where DOT3 fluids are recommended.

PRODUCT FEATURES & BENEFITS

- Good brake response
- Saves on maintenance
- Minimizes leakage and loss of pressure
- Longer fluid service life

APPLICATIONS

- All hydraulically operated motor vehicle braking systems (drum and disc types) for which a DOT3 or SAE J1703 fluid is specified
- Vehicles with anti-lock braking (ABS) systems
- Hydraulic clutch systems requiring conventional fluids Passenger cars, commercial road transport, off-highway vehicles, agricultural tractors and motorcycles



PERFORMANCE CHARACTERISTICS

OEM WHICH RECOMMENDS

DOT-3/SAE J1703



KEY PROPERTIES

Parameter	Typical value	Method
Appearance	Bright & clear	Visual
ASTM Colour	Max 2.0	ASTM D1500
Kinematic Viscosity		ASTM D445
	at (-40°C) min, cSt	1400
	at 100°C, cSt	2.5
pH value	7.5	ASTM D7946

Note: This document does not constitute specifications of the product

ENVIRONMENT, HEALTH AND SAFETY - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.

for further information on LAUGFS lubricants products and services call the LAUGFS lube tech advisory service on 94 11 5565800 Monday to Friday.