



# Supreme PETRA

**SAE OW-20**

**Fully Synthetic Hybrid Oil**

**API SP**

**ILSAC GF-6A**



**SUPREME PETRA, SAE OW-20**, is a Fully Synthetic Hybrid oil that delivers the latest technology to maximize the protection for the newest engines fueled by gasoline. It meets the highest API SP and ILSAC GF-6A performance and exceeds the most demanding requirements in relation to modern engine emission control systems.

## PRODUCT FEATURES & BENEFITS

- Low-speed pre ignition(LSPI) and timing chain wear protection
- Newest engine oil performance standard
- Greater fuel economy & fuel efficiency
- Enhance overall engine cleanliness and extend drain intervals
- Improved protection against engine wear

## APPLICATIONS

- Engines required SAE OW-20 viscosity grades as per manufactures recommendation.
- Latest gasoline engine technologies including high performance, turbo-charged gasoline direct injection (TGDI) and hybrids found in passenger cars, SUVs, light vans and trucks.



## PERFORMANCE CHARACTERISTICS

**SOCIETY OF AUTOMOTIVE ENGINEERS  
VISCOSITY CLASSIFICATION**

**SAE OW-20**

**AMERICAN PETROLEUM INSTITUTE  
PERFORMANCE CLASSIFICATION**

**API SP**

**ILSAC SPECIFICATION**

**ILSAC GF-6A**



## KEY PROPERTIES

Parameter	Typical value	Method
Appearance	Bright & clear	Visual
Colour	2.5-3.0	ASTM D1500
Kinematic Viscosity at 40°C cSt	35	ASTM D445
at 100°C cSt	7.0-9.0	
Viscosity index, min	175	ASTM D2270
Flash point, min °C	200	ASTM D92
Total base number, min mgKOH/g	6.50	ASTM D2896

Note: This document does not constitute specifications of the product

**ENVIRONMENT, HEALTH AND SAFETY** - Users should consult the MSDS, follow the precautions outlined and comply with all laws and regulations concerning its use and disposal.

All reasonable care has been taken to ensure that the information contained in this publication is accurate at the time of printing. However, the information is liable to variation in the event of subsequent changes in the blend, formulation, method of storage, improper handling and usage, etc.

for further information on LAUGFS lubricants products and services call the LAUGFS lube tech advisory service on 94 11 5565800 Monday to Friday.